



Features

- Up to 150 hours battery operation time » with rechargeable lipo battery
- Outdoor use » compact splash-proof housings for devices over 500 N
- Overload protection up to 500 % » with rugged aluminium die cast housing
- Optimized for hand-operated measurements » handles exactly in the measurement axis (optional)

Technical data

		Order No.:			
		FMI-B10B5	FMI-B10C1	FMI-B10C5	FMI-B10K1
Capacity F(nom)*	N	50	100	500	1000
Resolution**	N	0,05	0,1	0,5	1
Temperature coefficient*	%/K	0,02			
Reproducibility*	% F	0,06			
Repeatability*	% F	0,06			
Hysteresis*	% F	0,15			
Creeping (5min)*	% F	0,15			
Measuring principle		Bidirectional force sensor with strain gauges and high-speed ?-processor			
Nominal deflection*	mm	0,13	0,25	0,17	0,34
Measuring shaft		M6			
Max. operating force*	% F(nom)	120			
Breaking force*	% F(nom)	500			

Version: 10.08.2023

All data are valid at the time of generating this document. Technical changes or any other changes of the product may become effective at any time and without prior notice. All pictures and drawings are reference only. © PPT GmbH & Co. KG, Alluris® is a registered trade mark of PPT GmbH & Co. KG.

PPT GmbH & Co. KG | Basler Straße 65 | 79100 Freiburg | Germany

Tel: 0761 47979 3 | e-mail: info@alluris.de

www.alluris.de/en



Display	Type	5-digit LCD 12mm Autoreverse
	Refresh time (ms)	1000
Operation modes	Regular	N kg lb
	Peak (real-time)	-
	Limits + Statistics	-
Interface	USB	without
	Hirose	without
	Sensor	without
Power supply	Type	internal LiPo battery operation time 150h
Temperature (operation)*	°C	0 ... 40
Protection code (EN 60529)	Cable not plugged	Housing
Housing	Material	A-Druckguss
	LxWxH (mm)	150 x 82 x 29
	Weight (kg)	0,48
	Mounting	2xM4, 2xM5, adjusting holes D5(H7)

*) according VDI/VDE/DKD 2638 at 0,2 ...1 x F(nom) **) according DIN 1319-1

Scope of Supply

Force gauge with hook, flat head, notched head, conical head, VAC universal charger with EC-, UK- and US-wall plug connector, quickstart operation manual, protection case.

Version: 10.08.2023

All data are valid at the time of generating this document. Technical changes or any other changes of the product may become effective at any time and without prior notice. All pictures and drawings are reference only. © PPT GmbH & Co. KG, Alluris® is a registered trade mark of PPT GmbH & Co. KG.

PPT GmbH & Co. KG | Basler Straße 65 | 79100 Freiburg | Germany

Tel: 0761 47979 3 | e-mail: info@alluris.de

www.alluris.de/en