



Features

- Always ready for work » by independent photovoltaic energy supply
- Outdoor use » compact splash-proof housings for devices over 500 N
- Overload protection up to 500 % » with rugged aluminium die cast housing
- Optimized for hand-operated measurements » handles exactly in the measurement axis (optional)

Technical data

		Order No.:			
		FMI-S10B5	FMI-S10C1	FMI-S10C5	FMI-S10K1
Capacity F(nom)*	N	50	100	500	1000
Resolution**	N	0,05	0,1	0,5	1
Temperature coefficient*	% / K	125			
Reproducibility*	% F	0,06			
Repeatability*	% F	0,06			
Hysteresis*	% F	0,15			
Measuring principle		Bidirectional force sensor with strain gauges and high-speed ?-processor			
Nominal deflection*	mm	0,13	0,25	0,17	0,34
Measuring shaft		M6			
Max. operating force*	% F(nom)	120			
Breaking force*	% F(nom)	500			
Display	Type	5-digit 12mm Autoreverse			

Version: 10.08.2023

All data are valid at the time of generating this document. Technical changes or any other changes of the product may become effective at any time and without prior notice. All pictures and drawings are reference only. © PPT GmbH & Co. KG, Alluris® is a registered trade mark of PPT GmbH & Co. KG.

PPT GmbH & Co. KG | Basler Straße 65 | 79100 Freiburg | Germany

Tel: 0761 47979 3 | e-mail: info@alluris.de

www.alluris.de/en



Display	Update (ms)	100	
Operation modes	Regular	N kg lb	
	Peak (real-time)	-	
	Limits + Statistik	-	
Interface	USB	without	
	Hirose	without	
	Sensor	without	
Power supply	Type	Solar cell USB (max. 900 mA)	
	Connection	USB (socket)	
Temperature (operation)*	°C	0 ...40	
Protection code (EN 60529)	Cable not plugged	IP40	IP65
Housing	Material	Aluminium die cast	
	LxWxH (mm)	15 x 82 x 29	
	Weight (kg)	0,480	
	Mounting	2xM4, 2xM5, adjusting holes D5(H7)	

*) according VDI/VDE/DKD 2638 at 0,2 ...1 x F(nom) **) according DIN 1319-1

Scope of Supply

Force gauge with hook, flat head, notched head, conical head, quickstart operation manual, protection case.

Version: 10.08.2023

All data are valid at the time of generating this document. Technical changes or any other changes of the product may become effective at any time and without prior notice. All pictures and drawings are reference only. © PPT GmbH & Co. KG, Alluris® is a registered trade mark of PPT GmbH & Co. KG.

PPT GmbH & Co. KG | Basler Straße 65 | 79100 Freiburg | Germany

Tel: 0761 47979 3 | e-mail: info@alluris.de

www.alluris.de/en