



Features

- Fast compressive force test >> up to 1 kN durable construction
- Precise positioning >> Rack with 50mm feed per stroke
- Measurement exactly in the force axis >> Measuring instrument is connected vertically in measuring axis with lifting unit
- Very flexible >> Mounting of sample holder, adapter or grooved plate possible

Technical data

		Order No.:	
		FMT-110.00K1	FMT-110.01K1
Maximum Force	N	1000	
Stroke	mm	50	
Column length	mm	200	550
Application		Push	
Drive	Type	Manually	
Space for test object	Width (mm)	Variable Table top 200mm	
	Depth (mm)	118,5	
	Height (mm)	0 ... 200	
Mounting	Force Gauge	M10 connection with counter nut in force axis for FMI-B and FMI-S	
	Base plate	Standard M6 tapped hole in table top Mounting holes for T-slot plate or special tool	
Dimensions	LxWxH (mm)	280 x 200 x 575	280 x 200 x 925
Weight	kg	10,5	

Version: 14.03.2023

All data are valid at the time of generating this document. Technical changes or any other changes of the product may become effective at any time and without prior notice. All pictures and drawings are reference only. © PPT GmbH & Co. KG, Alluris® is a registered trade mark of PPT GmbH & Co. KG.

PPT GmbH & Co. KG | Basler Straße 65 | 79100 Freiburg | Germany

Tel: 0761 47979 3 | e-mail: info@alluris.de

www.alluris.de/en



Scope of Supply

Desktop unit with M10 mounting and lock nut for mounting Alluris force gauges, user manual, transport packaging. (Order force gauge and accessories for force introduction separately.)

Version: 14.03.2023

All data are valid at the time of generating this document. Technical changes or any other changes of the product may become effective at any time and without prior notice. All pictures and drawings are reference only. © PPT GmbH & Co. KG, Alluris® is a registered trade mark of PPT GmbH & Co. KG.

PPT GmbH & Co. KG | Basler Straße 65 | 79100 Freiburg | Germany

Tel: 0761 47979 3 | e-mail: info@alluris.de

www.alluris.de/en